



CapaFine Tex

Water based fine texture paint for exterior and interior use

Product Description

CapaFine Tex is a superior quality acrylic co-polymer water based fine grain texture paint for interior and exterior use. Suitable for achieving fine texture.

Properties:

- Solvent free and water thinnable
- Environment friendly and practically odourless
- Good hiding
- Excellent wet scrub resistance
- Can be over coated with water based or solvent based top coats

VOC Content: Low VOC

Volume Solids: 60 ± 2%

Degree of Gloss: Matt according to EN 13300

Colour: Standard as per the 3D System Plus colour cards. As the product can be tinted on the Caparol ColorExpress tinting system, virtually any colour can be matched and made available instantly.

Packaging: 5 kgs and 25 kgs

Shelf Life: 24 months

Application

Typical System:

Two uniform and generously applied coats of CapaFine Tex, thinned upto 10% with clean potable water, to suitably prepared substrate.

For a detailed system, refer to the relevant Method Statement.

Surface Preparation:

The substrate must be clean, sound, dry and free from dust, oil, grease and laitance.

For more details, refer to our Technical Advice Sheet.

Application Tools:

Brush, paint roller or spraying equipment

Spray Application by Hopper Gun:

Spraying angle: 90°
Nozzle size: 1 - 3mm
Pressure: 150 - 180 bars
Clean tools immediately after use with water.

Drying Time:

Touch dry in 1 hour; recoatable in 6 hours.

Spreading Rate:

Dry film thickness from 100 µm to 150 µm
Theoretical coverage from 2.0 m²/kg to 3.0 m²/kg

The above values relate to one coat application and are indicative only. Actual rate of consumption is best established through a trial application.

Health and Safety:

For detailed information on the health and safety hazards and precautions for use of this product, refer to our Technical Advice Sheet.

